

# Platform ladder

## Single-sided platform ladder

Made of aluminium.

Stable aluminium rectangular tube side-rails; steps 200 mm wide; platform size 600 x 800 mm; complete with handrail (option), as well as toe and knee rail; four self-locking castors, diam. 125 mm, height adjustable, three of two with arrestors. Comes in disassembled parts, detailed assembly instructions are enclosed. In keeping with Local Accident Prevention Rules, handrails on both sides are normally required as from a platform height of 1 m. Please order the compulsory accessories.

- Large stepping and standing surfaces:  
Safe, comfortable and fatigue-free working, also with tools and for a longer period of time
- Travelling with lockable castors:  
Fast and easy change of location
- Surface materials:  
Non-slip version; aluminium, wood, steel grating to be chosen, in most cases; suitable for the purpose of use
- Accessories:  
Handrails and central lifting gear for individual complementation

**Handrail  
(Option)**



Comfortable cm. 20 wide aluminium step

### TECHNICAL FEATURES

- Sturdy 200 mm width safety steps
- Distance between steps: 200 mm
- Guardrail height: 1.1 m
- Profiles dimensions: 58 mm x 25 mm
- Toeboard height: 60 mm
- 2 Self braking castors + 2 with brake (ø 125 mm)
- Platform in ribbed aluminium 60x80 cm
- Ramp inclination: 60°
- Inner front width : 600 mm
- Capacity: 150 Kg (including one person)

n°	m	m	m	m	m	Kg
3	1,72	0,72	2,72	0,77	1,24	38,00
4	1,96	0,96	2,96	0,82	1,41	41,00
5	2,20	1,20	3,20	0,88	1,58	45,00
6	2,44	1,44	3,44	0,94	1,75	48,00
7	2,68	1,68	3,68	1,00	1,92	52,00
8	2,92	1,92	3,92	1,06	2,09	56,00

Platform has to be considered as a step - Price doesn't include any handrail  
Technical features are indicative and can be modified without prior notice

### Accessories:

- Handrail on steps, either right or left
- Ladder without castors
- Wooden or steel grating steps



**GUARANTEE  
15 YEARS**



Via delle Groane, 13 - 24060 Bagnatica BG ITALY  
Tel. +39035681663 - Fax +39035676321  
Web: <http://www.svelt.it> - E-mail: [export@svelt.it](mailto:export@svelt.it)